



ENVIRO-DUO

Item Number 4684605

The powerful ENVIRO-DUO guarantees a smooth suction and filling process which, thanks to the air-cooled two-piston compressor, is equally stable throughout the entire process. The device is controlled with a button and safely extracts all common refrigerants up to and including A2L class.

- Powerful Compressor
- Oil and maintenance free compressor
- Equipped with overfill protection (80%) and self-cleaning mode
- Easy filter change
- Special compartment for moisture filters
- Factory revision and extensive spare parts available

Technical Data

Color	green bare
Connector A	1/4" SAE
Connector B	1/4" SAE
Working Pressure	558 psi
Operating Temperature Range	32 - 104 °F
Number of Pistons	2
Voltage	115 VAC
Frequency	60Hz
Protection Class	I
Ingression Protection	IP30
Energy Consumption	0.75 kW
Speed	1,450 rpm
Noise Level	70 dB(A)

Packaging	Cardboard box
Current	5A

Accessories

4493622	CA-CCL-60	Set of 3 charging hoses with ball valve 1/4" SAE, 60"/150 cm, blue, red & yellow, 1x straight 1/4" SAE, 1x straight with ball valve 1/4" SAE and core depressor
9881276	CCL-60	Set of 3 charging hoses, 1/4"SAE, 60"/150 cm blue, red & yellow, 1x straight 1/4" SAE, 1x bended 1/4" SAE with core depressor
4686959	REF-CYL	Lightweight refrigerant cylinder Capacity: 26.2l, connections: W 21.7 x 1/14"
9884820	K1-9/5	Adapter with gasket for large refrigerant cylinders, 5 pieces Thread: 21.8-14 G x 1/4" SAE
4687475	K1-9-LH/5	Adapter with gasket for flammable gases, 5 pieces Thread: W 21.8-14 G-LH x 1/4" SAE
9881865	10859	Venting hose, yellow, 5 m connection: 3/8" SAE